



## M-4023

### Biceps/Triceps

### VERSUS

#### TECHNICAL SPECIFICATIONS:

- 3 mm reinforced steel chassis.
- Anti oxidation treatment and special protection at welding points.
- 200<sup>o</sup> polyester powder paint in matt black.
- FIBABS drive pulleys, with ball bearings, made of highly friction resistant composite material and adapted to the cable diameter.
- 5 mm thick transmission cable, extremely flexible and resistant, with 7 strands of 19 wires. Includes tensioner for tension adjustment.
- Front and rear weight-stack cover, black color.
- Bottle holder.
- Seat and backrest non-deformable to pressure.
- Adjustable backrest.
- Antibacterial upholstery MRSA Standard, SANITIZED, Fireproof M2 Standard, UNE 1021, absence of solvents and noxious substances OEKO-TEX Standards. Red seams.
- Grips injected in non-porous and non-slip rubber material.
- Steel goniometer that allows you to adjust the position/angle of the start of the exercise.
- 5 kg weight plates with low friction bushings.
- Load selector with magnetic security system and clamping cable.
- Adjustable levelers.
- Workload: 110 kg.
- Descriptive pictogram of the exercise.
- Dimensions: 150x107x150 cm.
- EC declaration of conformity.
- Commercial use.

